



Cardiosave Intra-aortic Balloon Pump

A Revolution in Hemodynamic Support

This document is intended to provide information to an international audience outside of the US.

GETINGE 



Cardiosave

Hemodynamic Support, Flexibility, Portability

Available when and where you need it.

For patients in need of hemodynamic support, there's no time to lose. Cardiosave is a cutting edge device that reliably provides time proven Intra-aortic Balloon Counterpulsation Therapy. Getinge built the Cardiosave in a way to provide flexibility of use for both in-hospital and patient transfer conditions. With Cardiosave, hemodynamic support will be at the right time and in the right place.



Cardiosave Hybrid

Improved usability

The Cardiosave Hybrid is a portable and maneuverable IABP designed for easy conversion from hospital to transport configuration. It is designed for use with all Getinge IABs to maximize your hospital's investment.

- Backlit monitor display and touchscreen controls offer improved usability in low light
- Improved help screen navigation resolves issues quickly
- Better organized patient interface connections for straightforward setup
- Easy access to the connection panel for a better ergonomic experience
- Self-retracting power cord for staff safety
- Helium tank is stored out of sight and out of the way



Ensuring patient safety and comfort

Cardiosave Hybrid retains the familiar appearance and operation of previous Datascope/Maquet® Systems, but a closer look reveals features that improve performance for critically ill patients.

- Advanced algorithms offer easier management of the most complex patients
- Improved user interface is intuitive and easier to use, minimizing the risk of user errors
- Color coded and keyed connections ensure accurate setup
- Quieter than previous Datascope/Maquet pumps to alleviate patient anxiety





Enhanced pneumatics optimize diastolic augmentation

- Faster pneumatic speed allows the balloon to stay inflated longer during diastole.
 - HR 80 –10.0% faster than CS300 (normotensive patient)¹
 - HR 150 –16.4% faster than CS300 (normotensive patient)¹

- Console
- Cart
- Control monitor
- Helium tank
- Two batteries

Total weight: 51.8 kg /114 lbs

All weights ± 5%



¹Data on file

Cardiosave Rescue

Safely transport critically ill patients

Cardiosave Rescue is designed to meet the rigorous challenges of safely transporting critically ill patients by ambulance or air.

- Advanced algorithms offer easy management of complex patients
- Improved help screen navigation helps resolve issues quickly
- Overlapping control systems ensure safety
 - Hot-swappable lithium ion batteries
 - AC transport power supply is included
- Color coded and keyed connections ensure accurate setup



Improved physical characteristics for better inter-facility transports

- Lighter weight - approximately 40% of the weight of CS300 UTS²
- Smaller size - approximately 55% of the size of CS300 UTS²
- Backlit monitor display and touchscreen control improves usability in low light
- Better organized patient interface connections streamline setup
- Easier access to the control panel for ergonomic convenience



² Universal Transport System

Enhanced pneumatics optimize diastolic augmentation, and maximizes balloon inflation time during diastole

- Faster pneumatic speed
 - HR 80 – 10.0% faster than CS300 (normotensive patient)³
 - HR 150 – 16.4% faster than CS300 (normotensive patient)³



Specifications	
Weight Including Rescue console, control monitor and 2 batteries 24.1 kg /53 lbs All weights ± 5%	Dimensions Display Closed - Includes Rescue console and control monitor 57.2 cm high x 40.6 cm deep x 33.0 cm wide 22.5" high x 16" deep x 13" wide Display Open 90° - Includes Rescue console and control monitor 78.0 cm high x 40.6 cm deep x 33.0 cm wide 30.7" high x 16" deep x 13" wide All dimensions ± 5%. Dimensions include the Pneumatic Module




³Data on file

Safe, user-friendly interface

Cardiosave improves usability from the first touch. It incorporates a state-of-the-art liquid crystal display and touchscreen control. The large panel size, 24.58 cm x 18.43 cm / 9.68" x 7.26", 31 cm / 12.1" diagonal is used for both the upper waveform display and lower touch

screen control. This allows for larger patient display parameters, improved help screen navigation and customizable control screens to improve patient safety. The back-lit screens allow visibility in varying lighting conditions with no alternate light source required.







Screen is locked
to unlock press
Unlock Screen button

The screen locks to ensure patient safety by preventing accidental changes during transport.






Cardiosave Hybrid



Cardiosave Rescue

Ordering information

Product		Part Number
Cardiosave Hybrid - AS/NZS3112 Type I Plug		0998-00-0800-31
Cardiosave Hybrid - Type J Plug		0998-00-0800-32
Cardiosave Hybrid - Type D Plug		0998-00-0800-33
Cardiosave Hybrid - Type K Plug		0998-00-0800-34
Cardiosave Hybrid - Type M Plug		0998-00-0800-35
Cardiosave Hybrid - Type I Plug		0998-00-0800-45
Cardiosave Hybrid - Type G Plug		0998-00-0800-52
Cardiosave Hybrid - Type B Plug		0998-00-0800-53
Cardiosave Hybrid - Type E/F Plug		0998-00-0800-55

Ordering information

Product	Part Number
Cardiosave Rescue	0998-00-0800-83

**THIS PAGE IS THE INSIDE BACK COVER AND HAS
BEEN LEFT INTENTIONALLY BLANK.**



PN: 0002-08-1075 Rev C · ***GETINGE** *, Getinge, and Maquet are trademarks or registered trademarks of Getinge AB, its subsidiaries, or affiliates in the United States or other countries · Maquet is registered with the U.S. Patent and Trademark Office · Copyright 2019 Datascope Corp. · All rights reserved · 05/2019

This document is intended to provide information to an international audience outside of the US.

Getinge · 1300 MacArthur Blvd., Mahwah, NJ 07430, USA Phone: +1 201 995-8700 or 1 800 777-4222

Manufacturer: Datascope Corp. 1300 MacArthur Blvd., Mahwah, NJ 07430, USA

www.getinge.com